


AGRIMAX V- FLECTO

TIRE SIZE	VF 710/60 R 34
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	HOCHLEISTUNGSTRAKTOR / TRACTOR
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	173 D



ABMESSUNGEN US STANDARD

USA-CODE	94069507	RC (IN)	200.7
SW (IN)	27.9	RIM REC	DW 25 B
OD (IN)	67.6	RIM ALT	DW 24 B; DW 27 B
SLR (IN)	29.6	ECE	E11-106R-007201

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29
45	6660	7690	8740	9920	10820	11740	13040
FROM 40 TO 25	7310	8450	9600	10890	11890	12900	14330
20	7460	8630	9800	11110	12140	13160	14620
12	7610	8800	9990	11330	12380	13410	14900
5	8050	9300	10570	11980	13080	14190	15760
*UPTO 5 CYC WITH FRONT LOADER	10240	11840	13450	15260	16650	18050	20060
5 HT	7460	8630	9800	11110	12140	13160	14620

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.