

# XL GRIP (L3)

|                     |                                 |
|---------------------|---------------------------------|
| <b>TIRE SIZE</b>    | 17.5 - 25                       |
| <b>UM</b>           | IS STANDARD                     |
| <b>CONSTRUCTION</b> | ⊠ BIAS                          |
| <b>MACHINERY</b>    | RADLADER / RADLADER / PLANIERER |
| <b>VERSION</b>      | DUAL BEAD                       |
| <b>TIRE TYPE</b>    | TT                              |



## ABMESSUNGEN IS STANDARD

|                 |           |                 |       |
|-----------------|-----------|-----------------|-------|
| <b>OD (MM)</b>  | 1345      | <b>PR</b>       | 20    |
| <b>SLR (MM)</b> | 622       | <b>TRA CODE</b> | E3/L3 |
| <b>RC (MM)</b>  | 3980      |                 |       |
| <b>RIM REC</b>  | 14.00/1.5 |                 |       |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 4.00 | 5.75 |
|------------|------|------|
| 50         | 5000 | -    |
| 10         | -    | 8250 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.