


TRAC SUPER

| | |
|---------------------|--|
| TIRE SIZE | 500/50 R 17 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRATTORINO / TRATTORE |
| VERSIONE | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 147 D |



DIMENSIONI IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 490 | RIM REC | 16.00 |
| OD (MM) | 940 | ECE | E11-106R-007767 |
| SLR (MM) | 425 | SRI | 450 |
| RC (MM) | 2850 | | |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 1.2 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 | 3.6 | 4.0 | 4.5 |
|------------|------|------|------|------|------|------|------|------|------|
| 65 | 1200 | 1450 | 1665 | 1940 | 2185 | 2400 | 2645 | 2895 | 3075 |
| 40 | 1635 | 1970 | 2260 | 2640 | 2975 | 3265 | 3600 | 3935 | 4185 |
| 30 | 1815 | 2185 | 2510 | 2930 | 3300 | 3625 | 3995 | 4370 | 4645 |
| 10 | 2160 | 2605 | 2990 | 3490 | 3930 | 4320 | 4765 | 5205 | 5535 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.