

AS 504

TIRE SIZE	10.0/75 - 15.3
UM	IS STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК / ПРИЦЕП ДЛЯ ПОЛЕВЫХ РАБОТ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК
VERSION	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	106 A8
LI/SS FREE ROLLING	119 A8



РАЗМЕРЫ IS STANDARD

SW (MM)	264	RIM REC	9.00
OD (MM)	785	ECE	E11-106R-003509
SLR (MM)	360	PR	8
RC (MM)	2404	SRI	360

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	3.10
10 FR	1905
25 FR	1620
30 FR	1525
40 FR	1360
10 DW	1330
25 DW	1130
30 DW	1065
40 DW	950

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.