

EARTHMAX SR 45 H2



EARTHMAX
RADIAL OTR TIRES

EARTHMAX SR 45 H2

EARTHMAX SR 45 H2 is an All Steel radial tyre specifically designed for rigid haul trucks. The E-4 tread depth and the unique tread pattern ensure excellent wear minimizing vibration and noise. EARTHMAX SR 45 H2 is ideal for operations requiring traction and stability. The All Steel casing provides excellent resistance to snags and punctures and a long service life. Available in standard, heat-resistant and cut-resistant compounds.



	SIZE	TT/TL	TRA CODE	STAR RATING	LI/SS	RIM		TKPH (TK/H)	OW (MM) (mm)	OD (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (MM)	VERSION
						REC RIM	ALT RIM							
														
Ø35"	24.00 R 35	TL	E4	**	209 B	17.00/3.5	-	435	660	2180	978	6597	70	HRC
	24.00 R 35	TL	E4	***	212 B	17.00/3.5	---	435	660	2180	978	6597	70	HRC
	24.00 R 35	TL	E4	**	209 B	17.00/3.5	--	333	660	2180	978	6597	70	CR
	24.00 R 35	TL	E4	***	212 B	17.00/3.5	---	333	660	2180	978	6597	70	CR

HRC: HEAT RESISTANT COMPOUND, CR: CUT RESISTANT COMPOUND, STD: STANDARD

TECHNOLOGIES					PERFORMANCES			
								
								

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. BKT reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 23/09/2026

SIZE	TT/TL	TRA CODE	STAR RATING	LI/SS	RIM		TKPH (TK/H)	OW (MM) (mm)	OD (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (MM)	VERSION
					REC RIM	ALT RIM							
													
24.00 R 35	TL	E4	**	209 B	17.00/3.5	--	390	660	2180	978	6597	70	STD
24.00 R 35	TL	E4	***	212 B	17.00/3.5	---	390	660	2180	978	6597	70	STD

HRC: HEAT RESISTANT COMPOUND, CR: CUT RESISTANT COMPOUND, STD: STANDARD



TECHNOLOGIES				PERFORMANCES			
							
E4							
B							
212 kg							

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balakrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 23/09/2026