


RIDEMAX FL 693 M

| | |
|---------------------|------------------------------------------------------------------------------------------|
| | 500/45 R 22.5 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TANKER / RÖMÖRK / UYGULAMALI MAKINE |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| | 146 D ; 143 E |



UNDEFINED US STANDARD

| | | | |
|-----------------|----------|----------------|----------------|
| USA CODE | 94043767 | RC (IN) | 122.6 |
| SW (IN) | 19.8 | RIM REC | AG 16.00 |
| OD (IN) | 40.2 | ECE | E4-106R-000786 |
| SLR (IN) | 17.9 | | |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 15 | 17 | 23 | 29 | 35 | 41 | 46 | 52 | 58 |
|-----------|------|------|------|------|------|------|------|-------|-------|
| 45 | 2200 | 2470 | 3060 | 3490 | 4030 | 4570 | 4990 | 5470 | 6010 |
| 40 | 2410 | 2710 | 3370 | 3840 | 4430 | 5030 | 5490 | 6020 | 6610 |
| 30 | 2930 | 3280 | 4090 | 4650 | 5370 | 6080 | 6650 | 7290 | 8000 |
| 25 | 3300 | 3690 | 4600 | 5220 | 6030 | 6840 | 7470 | 8190 | 8990 |
| 15 | 3820 | 4290 | 5330 | 6060 | 7010 | 7950 | 8670 | 9510 | 10450 |
| 5 | 4350 | 4880 | 6070 | 6910 | 7980 | 9050 | 9890 | 10840 | 11900 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.