


AS 504

TIRE SIZE	6.00 - 16
UM	US STANDARD
CONSTRUCTION	 BIAS
MACHINERY	ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК / ПРИЦЕП ДЛЯ ПОЛЕВЫХ РАБОТ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК
VERSION	HD
TIRE TYPE	TT
LI/SS DRIVE WHEEL	91 A8
LI/SS FREE ROLLING	103 A8



РАЗМЕРЫ US STANDARD

USA CODE	94046812	RC (IN)	86.2
SW (IN)	6.5	RIM REC	4.00 E
OD (IN)	28.9	RIM ALT	4.50 E; 4½ K
SLR (IN)	13.5	ECE	E11-106R-005195

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	58
5 FR	2700
15 FR	2295
20 FR	2160
25 FR	1930
5 DW	1895
15 DW	1610
20 DW	1520
25 DW	1355

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.