


# RIDEMAX FL 693 M

TIRE SIZE	600/50 R 22.5
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TANKER / RÖMÖRK / UYGULAMALI MAKINE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	159 D ; 156 E



## BOYUTLAR IS STANDARD

SW (MM)	611	RIM REC	AG 20.00
OD (MM)	1172	ECE	E4-106R-000805
SLR (MM)	516	SRI	550
RC (MM)	3574		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	1480	1680	2040	2360	2720	3080	3320	3680	4000
65	1620	1840	2235	2585	2975	3370	3635	4025	4375
50	1960	2225	2705	3125	3605	4080	4395	4875	5295
40	2205	2500	3035	3515	4050	4585	4940	5475	5950
25	2560	2905	3530	4080	4705	5325	5740	6365	6915
10	2915	3310	4020	4650	5355	6065	6540	7245	7875

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.