

AGRIMAX RT 657

TIRE SIZE	540/65 R 34
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	КОМБАЙН ДЛЯ УБОРКИ ВИНОГРАДА / ТРАКТОР-ТЯГАЧ / КОМБАЙН
VERSION	SPECIAL
TIRE TYPE	TL
LI/SS	152 D ; 155 A8



РАЗМЕРЫ US STANDARD

USA CODE	94062645	RC (IN)	186.7
SW (IN)	20.9	RIM REC	W 16 L
OD (IN)	61.7	RIM ALT	W 18 L
SLR (IN)	28.0	ECE	E4-106R-000652

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	90	12	15	17	20	23	29	35
40	3760	4390	4940	5480	6030	6500	7210	7850
30	3960	4610	5180	5760	6340	6830	7570	8220
25	4100	4780	5390	5990	6580	7100	7860	8540
20	4330	5050	5680	6300	6940	7480	8290	9010
5 LT	5040	5890	6610	7350	8090	8720	9660	10490
5 HT	4330	5050	5680	6300	6940	7480	8290	9010

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.