

TR 882

TIRE SIZE	400/60 - 15.5
UM	US STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	ПРЕСС-ПОДБОРЩИК / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ПРИЦЕП / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ПРИЦЕП
VERSION	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	122 A8
LI/SS FREE ROLLING	134 A8



РАЗМЕРЫ US STANDARD

USA CODE	94019830	RC (IN)	102.6
SW (IN)	15.7	RIM REC	AG 13.00
OD (IN)	34.4	ECE	E11-106R-004330
SLR (IN)	14.9	PR	8

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	35
5 FR	6550
15 FR	5570
20 FR	5240
25 FR	4670
5 DW	4630
15 DW	3940
20 DW	3700
25 DW	3310

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.