


# AW 09

<b>TIRE SIZE</b>	<b>300/80 - 15.3</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	LANDWIRTSCHAFTLICHE GERÄTE / ANHÄNGER / HEUPRESSE / ERNTEMASCHINE / ERNTEMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	126 A8
<b>LI/SS FREE ROLLING</b>	138 A8



## ABMESSUNGEN US STANDARD

<b>USA-CODE</b>	94037902	<b>RC (IN)</b>	99.2
<b>SW (IN)</b>	11.6	<b>RIM REC</b>	9.00
<b>OD (IN)</b>	33.9	<b>ECE</b>	E4-106R-000377
<b>SLR (IN)</b>	14.8		

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	52
5 FR	7290
15 FR	6190
20 FR	5830
25 FR	5200
5 DW	5250
15	4460
20 DW	4200
25 DW	3750

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.