

# AS 504

**27X10 - 15.3****UM** US STANDARD**CONSTRUCTION**  BIAS**MACHINERY** TELESKOPIK YÜKLEYİCİ / TARLA  
RÖMORKU / UYGULAMALI MAKİNE /  
TELESKOPIK YÜKLEYİCİ**VERSION** STANDARD**TIRE TYPE** TL

95 A8

107 A8



## UNDEFINED US STANDARD

<b>USA CODE</b>	94039500	<b>RC (IN)</b>	81.5
<b>SW (IN)</b>	10.2	<b>RIM REC</b>	9.00
<b>OD (IN)</b>	27.4	<b>ECE</b>	E4-106R-002324
<b>SLR (IN)</b>	12.5	<b>PR</b>	8

## LOAD CAPACITY (LBS/TIRE)

<b>MPH / PSI</b>	<b>45</b>
<b>5 FR</b>	3010
<b>15 FR</b>	2560
<b>20 FR</b>	2400
<b>25 FR</b>	2150
<b>5 DW</b>	2130
<b>15 DW</b>	1810
<b>20 DW</b>	1710
<b>25 DW</b>	1520

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.