

FLOTATION 648

TIRE SIZE	800/45 - 26.5
UM	IS STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	ПРЕСС-ПОДБОРЩИК / КОМБАЙН / РАЗБРАСЫВАТЕЛЬ / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
VERSION	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	170 A8/167 B
LI/SS FREE ROLLING	183 A8/180 B



РАЗМЕРЫ IS STANDARD

SW (MM)	800	RIM REC	AG 28.00
OD (MM)	1393	ECE	E11-106R-004618
SLR (MM)	631	PR	20
RC (MM)	4185		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	2.60	2.70	2.80
10 FR	11730	11990	12250
20 FR	10560	10790	11025
30 FR	9385	9595	9800
40 FR	8380	8565	8750
50 FR	7540	7710	8000
10 DW	8045	8225	8400
20 DW	7240	7405	7560
30 DW	6435	6580	6720
40 DW	5745	5875	6000
50 DW	5170	5290	5450

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.