


# AGRIMAX RT 765

<b>TYRE SIZE</b>	<b>710/70 R 38</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRACTOR / IMPLEMENTS
<b>VERSION</b>	SPECIAL
<b>TL/TT</b>	TL
<b>LI/SS</b>	175 D ; 178 A8



## DIMENSIONS US STANDARD

<b>USA CODE</b>	94063536	<b>RC (IN)</b>	226.4
<b>SW (IN)</b>	28.2	<b>RIM REC</b>	DW 23 B
<b>OD (IN)</b>	77.1	<b>ECE</b>	E11-106R-006000
<b>SLR (IN)</b>	33.8	<b>TRA CODE</b>	R1W

## LOAD CAPACITY (LBS/TYRE)

MPH / PSI	9	12	15	17	20	23	29	35	41	47
40	5940	7000	8070	8980	10040	10960	12030	12930	14150	15210
30	6240	7350	8470	9420	10550	11510	12620	13580	14860	15970
25	6450	7610	8760	9750	10910	11900	13060	14050	15380	16530
20	6820	8060	9280	10330	11550	12600	13820	14870	16270	17490
5 LT	7960	9380	10810	12040	13460	14680	16110	17340	18970	20390
5 HT	6820	8060	9280	10330	11550	12600	13820	14870	16270	17490

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.