

AS 504

TIRE SIZE	16.0/70 - 20
UM	IS STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК / ПРИЦЕП ДЛЯ ПОЛЕВЫХ РАБОТ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК
VERSION	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	144 A8
LI/SS FREE ROLLING	156 A8



РАЗМЕРЫ IS STANDARD

SW (MM)	418	RIM REC	13
OD (MM)	1097	RIM ALT	12 SDC; 14; 13 SDC
SLR (MM)	487	ECE	E11-106R-004611
RC (MM)	3214	PR	16

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	4.00
10 FR	5600
25 FR	4760
30 FR	4480
40 FR	4000
10 DW	3920
25 DW	3330
30 DW	3135
40 DW	2800

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.