


# RIDEMAX FL 690

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | VF 900/65 R 32   |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | TANKBIL / SLÄPVAGN /<br>ARBETSFORDON / SLÄPVAGN  |
| <b>VERSION</b>      | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 197 D  |



## DIMENSIONER IS STANDARD

|                 |      |                |                 |
|-----------------|------|----------------|-----------------|
| <b>SW (MM)</b>  | 930  | <b>RIM REC</b> | DW 31 B         |
| <b>OD (MM)</b>  | 1986 | <b>RIM ALT</b> | DW 30; TW 30    |
| <b>SLR (MM)</b> | 838  | <b>ECE</b>     | E11-106R-006917 |
| <b>RC (MM)</b>  | 5878 | <b>SRI</b>     | 925             |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.8  | 1.2   | 1.6   | 2.0   | 2.4   | 2.8   |
|------------|------|-------|-------|-------|-------|-------|
| 70         | 5030 | 6435  | 7840  | 8890  | 10295 | 11695 |
| 65         | 5530 | 7070  | 8610  | 9770  | 11310 | 12850 |
| 50         | 6470 | 8270  | 10075 | 11430 | 13235 | 15035 |
| 40         | 7130 | 9120  | 11110 | 12605 | 14595 | 16580 |
| 10         | 9065 | 11595 | 14125 | 16020 | 18550 | 21075 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.