


AGRIMAX FORCE

IF 710/70 R 42

| | |
|--------------|--|
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | BIÇERDÖVER / YÜKSEK GÜÇTE TRAKTÖR / TRAKTÖR |
| VERSION | SPECIAL |
| TIRE TYPE | TL |
| | 179 D |



UNDEFINED US STANDARD

| | | | |
|----------|----------|---------|----------------|
| USA CODE | 94060078 | RC (IN) | 242.8 |
| SW (IN) | 28.2 | RIM REC | DW 25 B |
| OD (IN) | 81.1 | RIM ALT | DW 23 B |
| SLR (IN) | 36.2 | ECE | E4-106R-001830 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9 | 12 | 15 | 17 | 20 | 23 | 29 | 35 |
|---------------|-------|-------|-------|-------|-------|-------|-------|-------|
| 45 | 7300 | 8390 | 9630 | 10880 | 12120 | 13370 | 14600 | 15540 |
| FROM 40 TO 25 | 8020 | 9230 | 10590 | 11960 | 13330 | 14690 | 16060 | 17100 |
| 20 | 8340 | 9590 | 11010 | 12430 | 13860 | 15280 | 16700 | 17770 |
| 12 | 8660 | 9950 | 11430 | 12910 | 14380 | 15860 | 17340 | 18450 |
| 5 | 10180 | 11710 | 13450 | 15180 | 16920 | 18650 | 20390 | 21690 |
| UPTO 20 CYC | 10430 | 11990 | 13770 | 15540 | 17320 | 19090 | 20880 | 22210 |
| UPTO 10 CYC | 12430 | 14300 | 16410 | 18530 | 20650 | 22770 | 24890 | 26480 |
| UPTO 5 CYC | 13630 | 15670 | 18000 | 20330 | 22650 | 24980 | 27290 | 29040 |
| 5 HT | 8340 | 9590 | 11010 | 12430 | 13860 | 15280 | 16700 | 17770 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.