

# AW 705

|                           |  |
|---------------------------|--|
| <b>TIRE SIZE</b>          | <b>15.0/70 - 18</b>  |
| <b>UM</b>                 | US STANDARD  |
| <b>CONSTRUCTION</b>       | ⊠ BIAS   |
| <b>MACHINERY</b>          | BALPRESS / ARBETSFORDON /<br>SLÄPVAGN / SKÖRDEMASKIN /<br>ARBETSFORDON |
| <b>VERSION</b>            | STANDARD   |
| <b>TIRE TYPE</b>          | TL   |
| <b>LI/SS FREE ROLLING</b> | 145 A8   |



## DIMENSIONER US STANDARD

|                 |          |                |                |
|-----------------|----------|----------------|----------------|
| <b>USA CODE</b> | 94010110 | <b>RC (IN)</b> | 121.7          |
| <b>SW (IN)</b>  | 15.9     | <b>RIM REC</b> | 13.00          |
| <b>OD (IN)</b>  | 39.8     | <b>RIM ALT</b> | 13; W 13       |
| <b>SLR (IN)</b> | 17.6     | <b>ECE</b>     | E4-106R-001902 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 45   |
|-----------|------|
| 5 FR      | 8950 |
| 15 FR     | 7610 |
| 20 FR     | 7160 |
| 25 FR     | 6390 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.