

# MP 567

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | 14.5 - 20  |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> | ⊠ BIAS   |
| <b>MACHINERY</b>    | ARBETSFORDON / TELESKOPLASTARE<br>/ ARBETSFORDON /<br>TELESKOPLASTARE /<br>UNIVERSALFORDON |
| <b>VERSION</b>      | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |



## DIMENSIONER US STANDARD

|                 |          |                |                |
|-----------------|----------|----------------|----------------|
| <b>USA CODE</b> | 94038282 | <b>RC (IN)</b> | 130.5          |
| <b>SW (IN)</b>  | 14.2     | <b>RIM REC</b> | 11             |
| <b>OD (IN)</b>  | 43.9     | <b>RIM ALT</b> | 12 SDC         |
| <b>SLR (IN)</b> | 19.5     | <b>ECE</b>     | E4-54R-0022637 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 44   |
|-----------|------|
| 55        | 4940 |
| 25        | 5690 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.