

# AGRIMAX RT 855

|           |                                                                                 |
|-----------|---------------------------------------------------------------------------------|
| TIRE SIZE | 520/85 R 50                                                                     |
| UM        | IS STANDARD                                                                     |
| MACHINERY | PULVERIZADOR / VENDIMIADORA /<br>TRACTOR / COSECHADORA /<br>MAQUINARIA AGRÍCOLA |
| VERSIÓN   | STANDARD                                                                        |
| TIRE TYPE | TL                                                                              |
| LI/SS     | 165 A8/B                                                                        |

## DIMENSIONES IS STANDARD

|          |      |         |                 |
|----------|------|---------|-----------------|
| SW (MM)  | 516  | RIM REC | DW 16L          |
| OD (MM)  | 2154 | RIM ALT | DW 18 L         |
| SLR (MM) | 992  | ECE     | E11-106R-004895 |
| RC (MM)  | 6472 | SRI     | 1025            |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6  | 0.8  | 1.0  | 1.2  | 1.4  | 1.6  | 2.0  | 2.4  |
|------------|------|------|------|------|------|------|------|------|
| 50         | 2425 | 2785 | 3195 | 3605 | 4020 | 4430 | 4845 | 5150 |
| 40         | 2425 | 2785 | 3195 | 3605 | 4020 | 4430 | 4845 | 5150 |
| 30         | 2595 | 2980 | 3420 | 3865 | 4305 | 4745 | 5185 | 5515 |
| 10 LT      | 3250 | 3730 | 4285 | 4835 | 5390 | 5940 | 6495 | 6905 |
| 10 HT      | 2595 | 2980 | 3420 | 3865 | 4305 | 4745 | 5185 | 5515 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

