

# TR 273

|                     |                 |
|---------------------|-----------------|
| <b>TIRE SIZE</b>    | <b>28L - 26</b> |
| <b>UM</b>           | IS STANDARD     |
| <b>CONSTRUCTION</b> | ⊠ BIAS          |
| <b>MACHINERY</b>    | TRATOR          |
| <b>VERSÃO</b>       | DUAL BEAD       |
| <b>TIRE TYPE</b>    | TL              |
| <b>LI/SS</b>        | 160 A6          |



## DIMENSÕES IS STANDARD

|                 |      |                |                  |
|-----------------|------|----------------|------------------|
| <b>SW (MM)</b>  | 714  | <b>RIM REC</b> | DW 25 B          |
| <b>OD (MM)</b>  | 1673 | <b>RIM ALT</b> | DW 23 B          |
| <b>SLR (MM)</b> | 765  | <b>ECE</b>     | E11-106R-0010383 |
| <b>RC (MM)</b>  | 4861 | <b>PR</b>      | 16               |

## LOAD CAPACITY (KG/TIRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>1.90</b> |
| 30                | 4500        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.