

EARTHMAX SR 454



EARTHMAX
RADIAL OTR TIRES

EARTHMAX SR 454

EARTHMAX SR 454 is an All Steel radial tyre specially engineered for rigid dump trucks. The unique E-3 tread design and the special center groove provide enhanced lateral tractions and handling both on soft and muddy surfaces. This tyre is specially designed for higher speeds, long hauls at cooler operating temperature. The All Steel construction with multi-layer steel belts provide superior protection against shock and rock penetration.



	SIZE	TT/TL	TRA CODE	STAR RATING	LI/SS	RIM		TKPH	O.W. (mm)	OD (mm)	SLR (mm)	RC (mm)	THREAD DEPTH	VERSION
						REC RIM	ALT RIM							
														
Ø49"	27.00 R 49	TL	E3	**	223 B	19.50/4.0	--	640	740	2650	1187	8040	48	STD
	27.00 R 49	TL	E3	**	223 B	19.50/4.0	--	525	740	2650	1187	8040	48	CR
	27.00 R 49	TL	E3	**	223 B	19.50/4.0	--	725	740	2650	1187	8040	48	HRC
Ø51"	33.00 R 51	TL	E3	**	235 B	24.00/5.0	-	884	900	2990	1358	9085	49	CR

CR: CUT RESISTANT COMPOUND, STD: STANDARD, HRC: HEAT RESISTANT COMPOUND

TECHNOLOGIES				PERFORMANCES		
						
						
B	250 kg					

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. BKT reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 15/09/2026

	SIZE	TT/TL	TRA CODE	STAR RATING	LI/SS	RIM		TKPH	O.W. (mm)	OD (mm)	SLR (mm)	RC (mm)	THREAD DEPTH	VERSION
						REC RIM	ALT RIM							
														
	33.00 R 51	TL	E3	**	235 B	24.00/5.0	-	1215	900	2990	1358	9085	49	HRC
	36.00 R 51	TL	E3	**	241 B	26.00/5.0	-	1075	1010	3145	1393	9467	57	STD
	36.00 R 51	TL	E3	**	241 B	26.00/5.0	-	1215	1010	3145	1393	9467	57	HRC
	33.00 R 51	TL	E3	**	235 B	24.00/5.0	-	1023	900	2990	1358	9085	49	STD
Ø57"	40.00 R 57	TL	E3	**	250 B	29.00/6.0	32.00/6.0	1740	1115	3510	1583	10654	66	HRC
	40.00 R 57	TL	E3	**	250 B	29.00/6.0	32.00/6.0	1201	1115	3510	1583	10654	66	CR
	40.00 R 57	TL	E3	**	250 B	29.00/6.0	32.00/6.0	1462	1115	3510	1583	10654	66	STD

CR: CUT RESISTANT COMPOUND, STD: STANDARD, HRC: HEAT RESISTANT COMPOUND

TECHNOLOGIES				PERFORMANCES		
						
						
B	250 kg					

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balakrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 15/09/2026



TECHNOLOGIES		PERFORMANCES
  E3	 	  
 B	 250 kg	

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balakrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 15/09/2026