


AGRIMAX RT 600

TYRE SIZE	750/65 R 26
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRACTOR / IMPLEMENTS
VERSION	STANDARD
TYRE TYPE	TL
LI/SS	171 A8/B



DIMENSIONS IS STANDARD

SW (MM)	750	RIM REC	DW 24 B
OD (MM)	1636	RIM ALT	DW 23 B; DW 25 B
SLR (MM)	737	ECE	E11-106R-006182
RC (MM)	4987	SRI	775

LOAD CAPACITY (KG/TYRE)

KM/H / BAR	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2	3.4	3.8
50	2830	3260	3690	4000	4370	4860	5230	5720	6150	-	-
40	2830	3260	3690	4000	4370	4860	5230	5720	6150	-	-
30	3030	3495	3955	4285	4680	5205	5600	6125	6585	-	-
10 LT	3795	4370	4950	5360	5855	6515	7010	7670	8245	-	-
10 HT	3030	3495	3955	4285	4680	5205	5600	6125	6585	-	-
10 CYC	-	5240	5930	6425	7015	7810	8400	9190	9880	10010	10455

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.