


# AGRIMAX V-FLECTO

<b>TIRE SIZE</b>	<b>VF 710/60 R 42</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRACTEUR DE FORTE PUISSANCE / TRACTEUR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	173 D



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	710	<b>RIM REC</b>	DW 25 B
<b>OD (MM)</b>	1930	<b>RIM ALT</b>	DW 23 B; MW 25 B
<b>SLR (MM)</b>	860	<b>ECE</b>	E11-106R-002998
<b>RC (MM)</b>	5786	<b>SRI</b>	925

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6
70	3250	3785	4315	4850	5380	5915
FROM 65 TO 40	3575	4160	4745	5330	5915	6500
30	3645	4240	4835	5435	6030	6630
20	3715	4325	4930	5540	6150	6760
10	3930	4575	5215	5860	6505	7150
*UPTO 10 CYC WITH FRONT LOADER	5005	5820	6640	7460	8280	9100
10HT	3645	4240	4835	5435	6030	6630

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.