

# FLOTATION 648

<b>TIRE SIZE</b>	<b>600/50 - 22.5</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	BALPRESS / SKÖRDEMASKIN / SPRIDARE / SKÖRDEMASKIN / ARBETSFORDON
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	147 A8/144 B
<b>LI/SS FREE ROLLING</b>	159 A8/156 B



## DIMENSIONER US STANDARD

<b>USA CODE</b>	94006397	<b>RC (IN)</b>	137.8
<b>SW (IN)</b>	24.1	<b>RIM REC</b>	AG 20.00
<b>OD (IN)</b>	46.1	<b>ECE</b>	E4-106R-002312
<b>SLR (IN)</b>	20.1	<b>PR</b>	12

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	22	25	29
<b>5 FR</b>	11410	12280	13500
<b>10 FR</b>	10260	11060	12160
<b>20 FR</b>	9130	9830	10800
<b>25 FR</b>	8150	8770	9640
<b>30 FR</b>	7330	7890	8820
<b>5 DW</b>	8020	8630	9490
<b>10 DW</b>	7220	7760	8540
<b>20 DW</b>	6420	6900	7590
<b>25 DW</b>	5730	6160	6780
<b>30 DW</b>	5160	5540	6170

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.