


# AGRIMAX SPARGO

TIRE SIZE	VF 380/90 R 46 CFO
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRATOR
VERSÃO	STANDARD
TIRE TYPE	TL
LI/SS	173 D



## DIMENSÕES IS STANDARD

SW (MM)	390	RIM REC	DW 13 A
OD (MM)	1852	RIM ALT	W 13 A ; DW 12
SLR (MM)	846	ECE	E4-106R-000796
RC (MM)	5611	SRI	875

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1	1.2	1.4	1.6	1.8	2	2.2	2.4	2.6	2.8	3	3.2	3.4	3.6	3.8	4	4.2	4.4
70	2545	2840	3195	3490	3670	3845	3965	4085	4290	4500	4675	4855	5000	5150	5295	5445	5680	5915
FROM 65 TO 40	2795	3120	3510	3835	4030	4225	4355	4485	4715	4940	5135	5330	5495	5655	5820	5980	6240	6500
30	2855	3185	3585	3915	4115	4310	4445	4575	4810	5040	5240	5440	5605	5770	5935	6100	6365	6630
20	2910	3245	3655	3990	4195	4395	4530	4665	4905	5140	5345	5545	5715	5885	6055	6220	6490	6760
10*	3075	3435	3865	4220	4435	4650	4795	4935	5185	5435	5650	5865	6045	6225	6400	6580	6865	7150
UPTO 15 CYC.	3905	4360	4905	5355	5630	5900	6085	6265	6580	6900	7170	7445	7670	7900	8125	8350	8715	9075
UPTO 30 CYC.	3270	3650	4105	4485	4715	4940	5095	5245	5510	5780	6005	6235	6425	6615	6805	6995	7300	7600

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.