

FLOTATION 648

TIRE SIZE	600/55 - 22.5
UM	US STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	HEUPRESSE / ERNTEMASCHINE / STREUMASCHINE / ERNTEMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	156 A8/153 B
LI/SS FREE ROLLING	169 A8/166 B



ABMESSUNGEN US STANDARD

USA-CODE	94006427	RC (IN)	146.3
SW (IN)	23.6	RIM REC	AG 20.00
OD (IN)	48.4	ECE	E4-106R-001564
SLR (IN)	21.3	PR	16

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	32	35	38
5 FR	16240	17080	17900
10 FR	14620	15380	16110
20 FR	12980	13670	14320
25 FR	11600	12200	12790
30 FR	10440	10980	11680
5 DW	11200	11770	12350
10 DW	10090	10590	11110
20 DW	8960	9420	9880
25 DW	8000	8410	8820
30 DW	7200	7570	8050

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.