


# AGRIMAX V- FLECTO

<b>TIRE SIZE</b>	<b>VF 280/70 R 18</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRACTEUR DE FORTE PUISSANCE / TRACTEUR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	116 D



## DIMENSIONS US STANDARD

<b>CODE USA</b>	94076468	<b>RC (IN)</b>	99.0
<b>SW (IN)</b>	10.8	<b>RIM REC</b>	W 9
<b>OD (IN)</b>	33.4	<b>RIM ALT</b>	9
<b>SLR (IN)</b>	14.8	<b>ECE</b>	E11-106R-0010341

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
45	1370	1600	1820	2050	2270	2500
<b>FROM 40 TO 25</b>	1510	1760	2010	2260	2500	2760
20	1540	1800	2050	2300	2560	2810
12	1580	1830	2080	2350	2600	2870
5	1660	1940	2200	2480	2760	3030
<b>*UPTO 5 CYC WITH FRONT LOADER</b>	2120	2470	2810	3160	3510	3860
10HT	1540	1800	2050	2300	2560	2810

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.