

AW 711

TIRE SIZE	305/70 R 16.5
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	CEIFEIRA / IMPLEMENTOS AGRÍCOLAS / CEIFEIRA / IMPLEMENTOS AGRÍCOLAS
VERSÃO	STUBBLE RESISTANT
TIRE TYPE	TL
LI/SS	148 A8/B



DIMENSÕES IS STANDARD

SW (MM)	325	RIM REC	9.75
OD (MM)	851	ECE	E11-106R-002995
SLR (MM)	371	SRI	410
RC (MM)	2552		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	5.0
50	945	1230	1515	1735	2020	2300	2460	2710	2965	3150
40	945	1230	1515	1735	2020	2300	2460	2710	2965	3150
30	1060	1380	1695	1945	2260	2580	2755	3040	3320	3530
25	1125	1465	1800	2065	2400	2740	2925	3225	3525	3750
20	1195	1550	1910	2185	2545	2900	3100	3415	3735	3970
10	1325	1720	2120	2430	2825	3220	3440	3795	4150	4410

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.