


FL 637

560/560 R 22.5

UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	YAYICI / TANKER / RÖMORK / UYGULAMALI MAKINE
VERSION	STANDARD
TIRE TYPE	TL
	160 D



UNDEFINED US STANDARD

USA CODE	94074174	RC (IN)	130.9
SW (IN)	21.4	RIM REC	AG 16.00
OD (IN)	42.4	ECE	E11-106R-008660
SLR (IN)	19.7		

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	17	23	29	35	41	46	52	58	65	73	80	87
45	2180	2910	3640	4100	4730	5370	5920	6460	7100	7550	8000	8550	9090
40	2380	3170	3970	4460	5160	5850	6450	7040	7740	8230	8730	9330	9920
30	2890	3850	4810	5410	6250	7090	7800	8530	9370	9960	10570	11290	12000
25	3240	4320	5400	6070	7020	7970	8770	9590	10530	11200	11880	12690	13490
20	3600	4790	6000	6750	7790	8840	9740	10640	11690	12430	13180	14090	14980
15	3770	5030	6270	7050	8160	9250	10200	11130	12230	13020	13800	14740	15670
5	4290	5720	7140	8040	9290	10540	11610	12690	13930	14830	15720	16790	17860

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.