

# AGRIMAX RT 765

<b>TIRE SIZE</b>	<b>480/70 R 34</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	IRRORAZIONE / TRATTORE / VENDEMMIATRICE / MIETITREBBIA / ATTREZZI AGRICOLI
<b>VERSIONE</b>	SPECIAL
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	155 D



## DIMENSIONI IS STANDARD

<b>SW (MM)</b>	479	<b>RIM REC</b>	W 15 L
<b>OD (MM)</b>	1580	<b>RIM ALT</b>	W 14 L; W 16 L
<b>SLR (MM)</b>	728	<b>ECE</b>	E11-106R-005834
<b>RC (MM)</b>	4788	<b>SRI</b>	750

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2
65	1515	1785	2055	2290	2560	2790	3065	3295	3605	3875
50	1590	1875	2160	2405	2690	2935	3220	3460	3790	4070
40	1660	1955	2250	2505	2805	3060	3355	3610	3950	4245
30	1740	2055	2365	2635	2945	3215	3525	3795	4150	4460
10 LT	2030	2390	2755	3070	3430	3745	4105	4420	4835	5195
10 HT	1740	2055	2365	2635	2945	3215	3525	3795	4150	4460

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.