



PRINTED ON  
22-04-2026

## DATA SHEET

# EM 937 E3 (L)

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>14.00 - 25</b>  |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  BIAS |
| <b>MACHINERY</b>    | BACKHOE LOADER / LOADER  |
| <b>VERSION</b>      | ARAMID + STEEL BELTED  |
| <b>TIRE TYPE</b>    | TT   |



### DIMENSIONS US STANDARD

|                 |          |                 |           |
|-----------------|----------|-----------------|-----------|
| <b>USA CODE</b> | 94050734 | <b>RIM REC</b>  | 10.00/1.5 |
| <b>OD (IN)</b>  | 53.9     | <b>PR</b>       | 20        |
| <b>SLR (IN)</b> | 24.4     | <b>TRA CODE</b> | E3        |
| <b>RC (IN)</b>  | 161.6    |                 |           |

### LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 69    | 102   |
|-----------|-------|-------|
| 25        | 10500 | -     |
| 5         | -     | 18700 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.