

AS 504

| | |
|---------------------------|---|
| TIRE SIZE | 11.5/80 - 15.3 |
| UM | IS STANDARD |
| CONSTRUCTION | ❖ BIAS |
| MACHINERY | ELEVADOR TELESCÓPICO / EWMOLQUE PARA CAMPOS / MAQUINARIA AGRÍCOLA / ELEVADOR TELESCÓPICO |
| VERSIÓN | STANDARD |
| TIRE TYPE | TL |
| LI/SS DRIVE WHEEL | 114 A8 |
| LI/SS FREE ROLLING | 126 A8 |



DIMENSIONES IS STANDARD

| | | | |
|-----------------|------|----------------|----------------|
| SW (MM) | 290 | RIM REC | 9.00 |
| OD (MM) | 867 | ECE | E4-106R-001892 |
| SLR (MM) | 380 | PR | 8 |
| RC (MM) | 2540 | SRI | 410 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 2.70 |
|------------|------|
| 10 FR | 2380 |
| 25 FR | 2025 |
| 30 FR | 1905 |
| 40 FR | 1700 |
| 10 DW | 1650 |
| 25 DW | 1405 |
| 30 DW | 1320 |
| 40 DW | 1180 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.