

# AS 504

<b>TIRE SIZE</b>	<b>11.0/65 - 12</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	TELESKOPLADER / FELD-ANHÄNGER / LANDWIRTSCHAFTLICHE GERÄTE / TELESKOPLADER
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TT
<b>LI/SS DRIVE WHEEL</b>	101 A8
<b>LI/SS FREE ROLLING</b>	114 A8



## ABMESSUNGEN US STANDARD

<b>USA-CODE</b>	94019427	<b>RC (IN)</b>	81.6
<b>SW (IN)</b>	10.7	<b>RIM REC</b>	9.00
<b>OD (IN)</b>	27.6	<b>ECE</b>	E4-106R-002834
<b>SLR (IN)</b>	12.6	<b>PR</b>	8

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	42
5 FR	3640
15 FR	3100
20 FR	2910
25 FR	2600
5 DW	2550
15 DW	2160
20 DW	2040
25 DW	1820

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.