


# FORESTMAX

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>600/60 R 28</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | TRACTOR / FORESTRY   |
| <b>VERSION</b>      | STEEL BELTED   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 152 A8 ; 149 B   |



## DIMENSIONS US STANDARD

|                 |          |                |                  |
|-----------------|----------|----------------|------------------|
| <b>USA CODE</b> | 94512850 | <b>RC (IN)</b> | 169.9            |
| <b>SW (IN)</b>  | 22.4     | <b>RIM REC</b> | DW18L            |
| <b>OD (IN)</b>  | 56.3     | <b>RIM ALT</b> | DW20B            |
| <b>SLR (IN)</b> | 25.8     | <b>ECE</b>     | E11-106R-0010523 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI                 | 17   | 20   | 23   | 26    | 29    | 32    | 35    |
|---------------------------|------|------|------|-------|-------|-------|-------|
| 30                        | 4870 | 5450 | 5590 | 6160  | 6660  | 6880  | 7160  |
| 25                        | 5320 | 5950 | 6110 | 6730  | 7270  | 7520  | 7830  |
| 20                        | 5700 | 6370 | 6540 | 7210  | 7790  | 8050  | 8380  |
| 15                        | 5920 | 6610 | 6790 | 7480  | 8090  | 8360  | 8700  |
| 12                        | 6560 | 7330 | 7520 | 8290  | 8960  | 9260  | 9630  |
| 10                        | 7140 | 7980 | 8190 | 9030  | 9750  | 10070 | 10490 |
| 5                         | 7990 | 8930 | 9160 | 10100 | 10910 | 11280 | 11740 |
| <b>5 FORESTRY SERVICE</b> | -    | -    | -    | -     | -     | -     | 9630  |
| <b>0 FORESTRY SERVICE</b> | -    | -    | -    | -     | -     | -     | 18000 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.