

# AW 909

|                           |  |
|---------------------------|--|
| <b>TIRE SIZE</b>          | 15.0/55 - 17   |
| <b>UM</b>                 | IS STANDARD  |
| <b>CONSTRUCTION</b>       | ⊠ BIAS   |
| <b>MACHINERY</b>          | EMPACADORA DE HENO /<br>MAQUINARIA AGRÍCOLA / REMOLQUE<br>/ COSECHADORA / MAQUINARIA<br>AGRÍCOLA |
| <b>VERSIÓN</b>            | STANDARD   |
| <b>TIRE TYPE</b>          | TL   |
| <b>LI/SS FREE ROLLING</b> | 138 A8   |



## DIMENSIONES IS STANDARD

|                 |      |                |                 |
|-----------------|------|----------------|-----------------|
| <b>SW (MM)</b>  | 391  | <b>RIM REC</b> | 13.00           |
| <b>OD (MM)</b>  | 850  | <b>RIM ALT</b> | 13              |
| <b>SLR (MM)</b> | 377  | <b>ECE</b>     | E11-106R-003515 |
| <b>RC (MM)</b>  | 2490 | <b>PR</b>      | 12              |

## LOAD CAPACITY (KG/TIRE)

| <b>KM/H / BAR</b> | <b>3.10</b> |
|-------------------|-------------|
| 10 FR             | 3305        |
| 25 FR             | 2810        |
| 30 FR             | 2645        |
| 40 FR             | 2360        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.