

# AW 705

<b>TIRE SIZE</b>	16.0/70 - 20
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	❖ BIAS
<b>MACHINERY</b>	PRESĂ DE BALOTAT / MAȘINI DE IMPLEMENTARE / REMORCĂ / MAȘINĂ DE RECOLTARE / MAȘINI DE IMPLEMENTARE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TT
<b>LI/SS FREE ROLLING</b>	154 A8



## DIMENSIUNI US STANDARD

<b>USA CODE</b>	94010202	<b>RC (IN)</b>	124.2
<b>SW (IN)</b>	16.1	<b>RIM REC</b>	13.0
<b>OD (IN)</b>	42.3	<b>RIM ALT</b>	12 SDC; 13 SDC; 14
<b>SLR (IN)</b>	18.9	<b>ECE</b>	E11-106R-003368

## LOAD CAPACITY (LBS/TIRE)

<b>MPH / PSI</b>	<b>51</b>
5 FR	11570
15 FR	9840
20 FR	9260
25 FR	8270

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.