


AGRIMAX RT 765

| | |
|---------------------|--|
| TIRE SIZE | 420/70 R 28 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | SPRAYER / TRACTOR / VINEYARD HARVESTER / HARVESTER / IMPLEMENTS |
| VERSION | SPECIAL |
| TIRE TYPE | TL |
| LI/SS | 133 D |



DIMENSIONS IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 418 | RIM REC | W 13 |
| OD (MM) | 1349 | RIM ALT | W 12; W 14 L |
| SLR (MM) | 604 | ECE | E11-106R-005520 |
| RC (MM) | 4020 | SRI | 650 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 |
|------------|------|------|------|------|------|------|
| 65 | 1135 | 1320 | 1505 | 1690 | 1875 | 2060 |
| 50 | 1195 | 1390 | 1585 | 1780 | 1975 | 2165 |
| 40 | 1245 | 1450 | 1650 | 1855 | 2060 | 2260 |
| 30 | 1305 | 1520 | 1735 | 1945 | 2160 | 2370 |
| 10 LT | 1525 | 1770 | 2020 | 2270 | 2520 | 2765 |
| 10 HT | 1305 | 1520 | 1735 | 1945 | 2160 | 2370 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.