

# FLOTATION 648

<b>TIRE SIZE</b>	500/55 - 20
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	BALPRESS / SKÖRDEMASKIN / SPRIDARE / SKÖRDEMASKIN / ARBETSFORDON
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	138 A8/134 B
<b>LI/SS FREE ROLLING</b>	150 A8/146 B



## DIMENSIONER IS STANDARD

<b>SW (MM)</b>	508	<b>RIM REC</b>	16.00
<b>OD (MM)</b>	1058	<b>ECE</b>	E11-106R-003369
<b>SLR (MM)</b>	458	<b>PR</b>	12
<b>RC (MM)</b>	3153		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	2.00	2.20	2.40
10 FR	4215	4460	4690
20 FR	3795	4015	4220
30 FR	3370	3565	3750
40 FR	3010	3185	3350
50 FR	2710	2865	3000
10 DW	2970	3145	3305
20 DW	2670	2830	2975
30 DW	2375	2515	2645
40 DW	2120	2245	2360
50 DW	1910	2020	2120

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.