


FORESTMAX

TIRE SIZE	650/65 R 38
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRACTOR / TRANSPORTATOR
VERSION	STEEL BELTED
TIRE TYPE	TL
LI/SS	164 A8 ; 160 B



DIMENSIUNI US STANDARD

USA CODE	94074044	RC (IN)	215.2
SW (IN)	25.4	RIM REC	DW 20 B
OD (IN)	71.3	RIM ALT	DW21B; DW23B
SLR (IN)	32.8	ECE	E11-106R-008829

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	17	20	23	26	29	32	35
30	6750	7540	7740	8530	9230	9520	9920
25	7500	8380	8600	9480	10250	10580	11020
20	8020	8970	9200	10140	10970	11330	11790
15	8320	9300	9550	10530	11380	11750	12230
12	9230	10310	10570	11660	12600	13020	13560
10	10050	11230	11520	12700	13730	14190	14770
5	11240	12570	12900	14220	15370	15870	16530
5 FORESTRY SERVICE	-	-	-	-	-	-	13560
0 FORESTRY SERVICE	-	-	-	-	-	-	25350

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.