


AGRIMAX SPARGO SB

| | |
|---------------------|--|
| TIRE SIZE | VF 270/95 R 38 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRATTORE / IRRORAZIONE |
| VERSIONE | STEEL BELTED |
| TIRE TYPE | TL |
| LI/SS | 151 D |



DIMENSIONI IS STANDARD

| | | | |
|-----------------|------|----------------|------------------|
| SW (MM) | 280 | RIM REC | W9 |
| OD (MM) | 1491 | ECE | E11-106R-0010500 |
| SLR (MM) | 692 | SRI | 725 |
| RC (MM) | 4546 | | |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 1.0 | 1.2 | 1.4 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 | 3.6 | 4.0 |
|----------------------|------|------|------|------|------|------|------|------|------|------|
| 70 | 1480 | 1665 | 1855 | 2010 | 2230 | 2355 | 2575 | 2795 | 2985 | 3140 |
| FROM 65 TO 40 | 1625 | 1830 | 2040 | 2210 | 2450 | 2590 | 2830 | 3075 | 3280 | 3450 |
| 30 | 1655 | 1870 | 2080 | 2255 | 2500 | 2640 | 2890 | 3135 | 3345 | 3520 |
| 20 | 1690 | 1905 | 2120 | 2300 | 2550 | 2695 | 2945 | 3200 | 3415 | 3590 |
| 10 | 1785 | 2015 | 2240 | 2430 | 2695 | 2850 | 3115 | 3380 | 3610 | 3795 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.