


# AGRIMAX ELOS

<b>TIRE SIZE</b>	<b>480/70 R 34</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRATTORE
<b>VERSIONE</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	155 A8 ; 155 B



## DIMENSIONI US STANDARD

<b>CODICE USA</b>	94070299	<b>RC (IN)</b>	191.7
<b>SW (IN)</b>	19.7	<b>RIM REC</b>	W 15 L
<b>OD (IN)</b>	63.2	<b>RIM ALT</b>	W 16 L; W 14 L
<b>SLR (IN)</b>	28.9	<b>ECE</b>	E11-106R-007532

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35	41	46
<b>30</b>	3340	3940	4530	5050	5640	6150	6760	7440	8040	8540
<b>25</b>	3340	3940	4530	5050	5640	6150	6760	7440	8040	8540
<b>20</b>	3570	4210	4850	5400	6040	6590	7230	7970	8610	9150
<b>5 LT</b>	4480	5270	6070	6770	7560	8260	9050	9960	10770	11450
<b>5 HT</b>	3570	4210	4850	5400	6040	6590	7230	7970	8610	9150

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.