


AGRIMAX TURF RT 333

TIRE SIZE	480/70 R 34
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	SKÖRDEMASKIN FÖR VINGÅRD / SKÖRDEMASKIN FÖR FRUKTODLING / LITEN TRAKTOR / TRAKTOR / SKÖRDEMASKIN
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	149 A8 ; 149 B



DIMENSIONER IS STANDARD

SW (MM)	490	RIM REC	W 15 L
OD (MM)	1580	RIM ALT	W 14 L ; W 16 L
SLR (MM)	723	ECE	E11-106R-009042
RC (MM)	4785	SRI	750

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
50	1530	1755	2015	2275	2535	2795	3055	3250
40	1530	1755	2015	2275	2535	2795	3055	3250
30	1640	1880	2160	2440	2715	2995	3275	3480
10 LT	2050	2355	2705	3050	3400	3750	4095	4355
10 HT	1640	1880	2160	2440	2715	2995	3275	3480

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.