


# FL 630 SUPER

<b>TIRE SIZE</b>	<b>600/50 R 22.5</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	ÉPANDEUR / VÉHICULE CITERNE / REMORQUE / OUTILLAGE AGRICOLE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	159 D



## DIMENSIONS US STANDARD

<b>CODE USA</b>	94060900	<b>RC (IN)</b>	139.1
<b>SW (IN)</b>	24.1	<b>RIM REC</b>	AG 20.00
<b>OD (IN)</b>	46.1	<b>ECE</b>	E11-106R-005992
<b>SLR (IN)</b>	20.4		

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	15	17	23	29	35	41	46	52	58
45	3210	3600	4490	5100	5890	6680	7300	8000	8780
40	3530	3960	4930	5600	6470	7330	8010	8780	9645
30	4270	4790	5960	6780	7830	8870	9690	10630	11670
25	4790	5380	6690	7620	8800	9980	10890	11940	13120
15	5570	6260	7780	8850	10220	11600	12650	13880	15240
5	6340	7120	8860	10070	11640	13190	14420	15810	17360

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.