


# POWERTRAILER SR 331

<b>TIRE SIZE</b>	<b>560/60 R 22.5</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRAILER / IMPLEMENTS / TANKER
<b>VERSION</b>	IMPLEMENT
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	165 D



## DIMENSIONS IS STANDARD

<b>OD (MM)</b>	1245	<b>RIM ALT</b>	17.00; AG18.00
<b>SLR (MM)</b>	565	<b>ECE</b>	E11-106R-0010087
<b>RC (MM)</b>	3775	<b>SRI</b>	600
<b>RIM REC</b>	AG 16.00		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	3.2	3.6	4	4.5	5
10	6860	7505	8255	8810	9270
25	6020	6590	7245	7735	8135
40	5180	5670	6235	6655	7005
50	4610	5045	5550	5925	6230
65	3810	4170	4585	4895	5150
70	3465	3795	4170	4455	4685

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.