


# AGRIMAX RT 657

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>600/65 R 28</b>   |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | MACHINE À VENDANGER / TRACTEUR<br>/ MOISSONNEUSE   |
| <b>VERSION</b>      | SPECIAL  |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 154 D ; 157 A8   |



## DIMENSIONS IS STANDARD

|                 |      |                |                |
|-----------------|------|----------------|----------------|
| <b>SW (MM)</b>  | 611  | <b>RIM REC</b> | DW 20 B        |
| <b>OD (MM)</b>  | 1491 | <b>RIM ALT</b> | W 18 L         |
| <b>SLR (MM)</b> | 670  | <b>ECE</b>     | E4-106R-000621 |
| <b>RC (MM)</b>  | 4470 | <b>SRI</b>     | 700            |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR   | 0.6  | 0.8  | 1.0  | 1.2  | 1.4  | 1.6  | 2.0  | 2.4  |
|--------------|------|------|------|------|------|------|------|------|
| <b>65</b>    | 1800 | 2100 | 2365 | 2625 | 2890 | 3115 | 3450 | 3750 |
| <b>50</b>    | 1895 | 2210 | 2485 | 2760 | 3035 | 3275 | 3625 | 3940 |
| <b>40</b>    | 1980 | 2310 | 2600 | 2890 | 3180 | 3425 | 3795 | 4125 |
| <b>30</b>    | 2075 | 2420 | 2720 | 3025 | 3325 | 3585 | 3970 | 4315 |
| <b>10 LT</b> | 2415 | 2815 | 3170 | 3520 | 3870 | 4175 | 4625 | 5025 |
| <b>10 HT</b> | 2075 | 2420 | 2720 | 3025 | 3325 | 3585 | 3970 | 4315 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.