

# AS 509

<b>TIRE SIZE</b>	<b>550/45 - 22.5</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	BALPRESS / ARBETSFORDON / SLÄPVAGN / SKÖRDEMASKIN / ARBETSFORDON
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	141 A8/137 B
<b>LI/SS FREE ROLLING</b>	153 A8/149 B



## DIMENSIONER US STANDARD

<b>USA CODE</b>	94064878	<b>RC (IN)</b>	128.0
<b>SW (IN)</b>	21.3	<b>RIM REC</b>	AG 16.00
<b>OD (IN)</b>	41.9	<b>ECE</b>	E11-106R-006445
<b>SLR (IN)</b>	18.9	<b>PR</b>	12

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	22	26	30
<b>5 FR</b>	9260	10300	11260
<b>10 FR</b>	8330	9260	10140
<b>20 FR</b>	7410	8230	9020
<b>25 FR</b>	6610	7350	8050
<b>30 FR</b>	5950	6610	7160
<b>5 DW</b>	6530	7260	7950
<b>10 DW</b>	5870	6540	7150
<b>20 DW</b>	5220	5820	6360
<b>25 DW</b>	4660	5190	5680
<b>30 DW</b>	4200	4670	5070

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.