


# FL 630 SUPER

|                     |  |
|---------------------|--|
|                     | <b>650/55 R 26.5</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | YAYICI / TANKER / RÖMORK / UYGULAMALI MAKINE   |
| <b>VERSION</b>      | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |
|                     | 169 D  |



## UNDEFINED US STANDARD

|                 |          |                |                |
|-----------------|----------|----------------|----------------|
| <b>USA CODE</b> | 94038855 | <b>RC (IN)</b> | 167.6          |
| <b>SW (IN)</b>  | 25.4     | <b>RIM REC</b> | AG 20.00       |
| <b>OD (IN)</b>  | 54.7     | <b>ECE</b>     | E4-106R-000806 |
| <b>SLR (IN)</b> | 24.7     |                |                |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 12   | 15   | 17   | 23    | 29    | 35    | 41    | 46    | 52    | 58    |
|-----------|------|------|------|-------|-------|-------|-------|-------|-------|-------|
| 45        | 3730 | 4310 | 4890 | 5940  | 6880  | 7930  | 8970  | 9670  | 10710 | 11640 |
| 40        | 4100 | 4740 | 5380 | 6530  | 7550  | 8700  | 9850  | 10610 | 11770 | 12790 |
| 30        | 4960 | 5730 | 6500 | 7900  | 9140  | 10530 | 11930 | 12850 | 14240 | 15480 |
| 25        | 5570 | 6440 | 7310 | 8870  | 10270 | 11840 | 13400 | 14440 | 16000 | 17390 |
| 15        | 6470 | 7480 | 8490 | 10310 | 11930 | 13750 | 15560 | 16780 | 18590 | 20200 |
| 5         | 7370 | 8520 | 9670 | 11870 | 13580 | 15650 | 17720 | 19110 | 21170 | 23010 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.