

# AGRIMAX FORCE

|              |                                                                                          |
|--------------|------------------------------------------------------------------------------------------|
| TIRE SIZE    | IF 650/75 R 38                                                                           |
| UM           | US STANDARD                                                                              |
| CONSTRUCTION |  RADIAL |
| MACHINERY    | ERNTemaschine /<br>HOCHLEISTUNGSTRAKTOR / TRACTOR                                        |
| VERSION      | STANDARD                                                                                 |
| TIRE TYPE    | TL                                                                                       |
| LI/SS        | 175 D                                                                                    |



## ABMESSUNGEN US STANDARD

|          |          |         |                 |
|----------|----------|---------|-----------------|
| USA-CODE | 94069477 | RC (IN) | 228.4           |
| SW (IN)  | 25.6     | RIM REC | DW 23 B         |
| OD (IN)  | 76.4     | RIM ALT | DW 21 B         |
| SLR (IN) | 34.1     | ECE     | E11-106R-007385 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI     | 9     | 12    | 15    | 17    | 20    | 23    | 29    | 35    |
|---------------|-------|-------|-------|-------|-------|-------|-------|-------|
| 45            | 6520  | 7490  | 8590  | 9700  | 10810 | 11920 | 13020 | 13850 |
| FROM 40 TO 25 | 7160  | 8230  | 9440  | 10650 | 11880 | 13090 | 14310 | 15220 |
| 20            | 7450  | 8560  | 9830  | 11090 | 12360 | 13620 | 14890 | 15830 |
| 12            | 7730  | 8890  | 10200 | 11510 | 12820 | 14150 | 15460 | 16440 |
| 5             | 9090  | 10440 | 11990 | 13540 | 15080 | 16630 | 18170 | 19330 |
| UPTO 20 CYC   | 9310  | 10690 | 12270 | 13850 | 15440 | 17010 | 18600 | 19780 |
| UPTO 10 CYC   | 11090 | 12750 | 14630 | 16520 | 18400 | 20290 | 22170 | 23580 |
| UPTO 5 CYC    | 12160 | 13970 | 16040 | 18110 | 20180 | 22250 | 24320 | 25860 |
| 5 HT          | 7450  | 8560  | 9830  | 11090 | 12360 | 13620 | 14890 | 15830 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.