



IS standard



GROWING TOGETHER

TR 273



PRODUCT DATA SHEET

TR 273



TR 273 is a tractor tire suitable for soil tillage and specifically designed to provide maximum performance on wet and moist soil. In these soil conditions, a tire is required to offer superior grip and enhanced self-cleaning properties. TR 273 perfectly meets all these characteristics.



Bias

R-2

A6

164

Technologies



Extra Deep Tread

Performance



Traction



For muddy ground



Self-Cleaning



Durability



Cut and Chip Resistance

| | Tire size | RIM | | S.W. (mm) | O.D. (mm) | SLR (mm) | RC (mm) | Version | PR | Type | LI/SS |
|----------------|-----------|----------------------|---------|--------------|--------------|-------------|------------|---------|----|------|--------|
| | | Rec. | Alt. | | | | | | | | |
| Ø 24" | 12.4 - 24 | W 11 | W 10 | 315 | 1195 | 550 | 3722 | STD | 8 | TT | 121 A6 |
| | 13.6 - 24 | W 12 | W 11 | 350 | 1240 | 570 | 3795 | STD | 8 | TT | 123 A6 |
| | 14.9 - 24 | W 13 | W 12 | 380 | 1310 | 595 | 4044 | STD | 8 | TT | 128 A6 |
| | 14.9 - 24 | W 13 | W 12 | 380 | 1310 | 595 | 4044 | STD | 10 | TT | 132 A6 |
| Ø 26" | 18.4 - 26 | W 16 | W 15 | 470 | 1490 | 673 | 4534 | STD | 12 | TT | 146 A6 |
| | 23.1 - 26 | DW 20 A ; DW 20 B | - | 590 | 1655 | 737 | 5053 | STD | 10 | TT | 149 A6 |
| | 23.1 - 26 | DW 20 A ; DW 20 B | - | 590 | 1655 | 737 | 5053 | STD | 12 | TT | 153 A6 |
| | 23.1 - 26 | DW 20 A ; DW 20 B | - | 590 | 1655 | 737 | 5053 | STD | 14 | TT | 156 A6 |
| | 28 L - 26 | DW 25 B | DW 23 B | 714 | 1673 | 765 | 4861 | DB | 16 | TL | 160 A6 |
| NEWSIZE | | | | | | | | | | | |
| Ø 28" | 14.9 - 28 | W 13 | W 12 | 385 | 1410 | 651 | 4368 | STD | 8 | TT | 130 A6 |
| Ø 30" | 16.9 - 30 | W 15 L | W 14 L | 435 | 1530 | 706 | 4800 | STD | 12 | TT | 143 A6 |
| | 18.4 - 30 | W 16 L | W 15 L | 465 | 1585 | 723 | 4924 | STD | 12 | TT | 149 A6 |
| | 23.1 - 30 | DW 20 A ; DW 20 B | - | 590 | 1748 | 794 | 5356 | STD | 10 | TT | 151 A6 |
| | 23.1 - 30 | DW 20 A ; DW 20 B | - | 590 | 1748 | 794 | 5356 | STD | 14 | TT | 157 A6 |

STD: Standard - DB: Dual Bead

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference



Bias



A6



Technologies



Extra Deep Tread

Performance



Traction



For muddy ground



Self-Cleaning



Durability



Cut and Chip Resistance



| | Tire size | RIM | | S.W. (mm) | O.D. (mm) | SLR (mm) | RC (mm) | Version | PR | Type | LI/SS |
|-------|----------------|----------------------|-------------------------------|--------------|--------------|-------------|------------|---------|----|------|--------|
| | | Rec. | Alt. | | | | | | | | |
| Ø 32" | 30.5 L - 32 | DH 27 B | DW 27 B | 765 | 1865 | - | - | STD | 14 | TL | 164 A6 |
| | NEWSIZE | | | | | | | | | | |
| Ø 34" | 18.4 - 34 | DW 16 A | W 16 L ; W 15 L DW 15 L | 475 | 1701 | 775 | 5253 | STD | 12 | TT | 150 A6 |
| | 23.1 - 34 | DW 20 A ; DW 20 B | - | 590 | 1850 | 833 | 5634 | STD | 10 | TT | 153 A6 |
| | 23.1 - 34 | DW 20 A ; DW 20 B | - | 590 | 1850 | 831 | 5674 | STD | 14 | TT | 160 A6 |
| Ø 38" | 18.4 - 38 | W 16 | W 15 | 465 | 1800 | 822 | 5579 | STD | 12 | TT | 152 A6 |
| | 20.8 - 38 | W 18 A ; W 18 L | DD 18 ; DW 18 A | 533 | 1886 | - | - | STD | 12 | TT | 156 A6 |
| | NEWSIZE | | | | | | | | | | |

STD: Standard



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference